

## Model 1036-00

## Suspended Ceiling Enclosure

The Model 1036-00 wireless LAN access point enclosure is a locking, ceiling tile insert, designed to accommodate access points from most manufacturers. This aesthetic, white powder coated steel enclosure has openings in the ventilated door for up to six antennas. Installation requires a square opening to be cut into the ceiling tile. The enclosure is supported by two back-side tile bridges.



Model 1036-00 shown with Cisco 1242 AP (not included) and (2) optional 34-ZDUAL antennas (not included)

### Specifications:

- Ceiling tile insert, accommodates one access point from most manufacturers
- UL Listed and designed to meet NEC300-22 and 300-23 for plenum installations
- OSHPD approved, OPA # 1638
- Accommodates up to (6) external antennas using the bulkhead connector kit for dipole antennas (Oberon P/N 35-BULKHD-KIT) or Oberon 34-ZDUAL or 34-DMDUAL antennas
- Construction: Textured white powder-coated steel, 16 ga. backbox, 14 ga. door
- Fully hinged locking door, keyed alike
- Size: Flange is 14" x 14", access point enclosure is 12" x 12" x 3¾" deep
- Weight: 11lbs (not including access point or antennas)
- Enclosure must be supported by the building ceiling structural system, not tile gridwork.

### Model 1036-00 Includes:

- Universal mounting plate for most manufacturers access point, mounting screws & hardware
- (4) Suspension wires, and (2) tile bridges
- (2) ¾" trade clamp connectors for power and data cable openings in the back-box
- Mounting Instructions