

The model 1053-T wireless LAN access point enclosure is a locking 2' x 2' ceiling tile enclosure designed specifically for the Cisco 1250, 1260, and 3500e series wireless access points. This aesthetic, white powder coated steel enclosure has mounting features in the door for installation of the Cisco 802.11n antennas, simplifying installation & optimizing wireless coverage. The 1053-T features a 3/8" bevel in the flange around the perimeter, to match "tegular" ceiling tiles commonly used in new construction and renovations. No ceiling tile cuts are required for installation.



Model 1053-T shown with Cisco 1252 AP (not included) and Cisco AIR-ANT2430V-R and AIR-ANT5140V-R antennas (not included)

Specifications:

- Ceiling tile enclosure specifically designed for Cisco 1250, 1260, and 3500e series APs
- Features a 3/8" bevel in the flange around the perimeter, to match "tegular" ceiling tiles
- UL Listed and designed to meet NEC300-22 and 300-23 for plenum installations
- OSHPD approved, OPA # 1638
- Door mounting features for Cisco P/N AIR-ANT2430V-R and AIR-ANT5140V-R antennas only
- Construction: textured white powder coated steel
- Fully hinged locking door, keyed alike
- Size: Flange is 2' x 2', AP Enclosure is 13" x 13" x 5" deep
- Weight: 15lbs (not including access point or antennas)
- Enclosure must be supported by the building ceiling structural system, not tile gridwork.

Model 1053-T includes:

- Snap lock mounting plate for the Cisco 1250 access point
- Three light pipes to view access point LED's externally
- (4) Suspension wires
- (2) 3/4" trade clamp connectors for power and data cable openings in the back-box
- Mounting Instructions